



## SAFETY DATA SHEET

151 MATT BLACK PAINT - LOW VOC

Page: 1  
Compilation date: 22/07/2010  
Revision date: 14/08/2015  
Revision No: 8

### Section 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

**Product name:** 151 MATT BLACK PAINT - LOW VOC

**Product code:** DY024A

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Use of substance / mixture:** SU 21 - Consumer Uses.

PC9a: Coatings and paints, thinners, paint removers.

#### 1.3. Details of the supplier of the safety data sheet

**Company name:** 151 Products Limited  
The Old School House  
39 Bengal Street  
Manchester  
M4 6AF  
UK

**Tel:** 0161 839 5949

**Fax:** 0161 839 5493

**Email:** [fereshteh@151.co.uk](mailto:fereshteh@151.co.uk)

#### 1.4. Emergency telephone number

### Section 2: Hazards identification

#### 2.1. Classification of the substance or mixture

**Classification under CLP:** Asp. Tox. 1: H304; Aquatic Chronic 3: H412; Flam. Liq. 3: H226; Skin Irrit. 2: H315

**Most important adverse effects:** Flammable liquid and vapour. May be fatal if swallowed and enters airways. Causes skin irritation. Harmful to aquatic life with long lasting effects.

#### 2.2. Label elements

##### Label elements:

**Hazard statements:** H226: Flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

H412: Harmful to aquatic life with long lasting effects.

**Hazard pictograms:** GHS02: Flame

GHS07: Exclamation mark

GHS08: Health hazard



[cont...]

# SAFETY DATA SHEET

151 MATT BLACK PAINT - LOW VOC

Page: 2

**Signal words:** Danger

**Precautionary statements:** P102: Keep out of reach of children.

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P241: Use explosion-proof electrical/ventilating/lighting/.. equipment.

P280: Wear protective gloves.

P301+310: IF SWALLOWED: Immediately call a POISON CENTER/doctor/NHS111.

P302+352: IF ON SKIN: Wash with plenty of water/.

## 2.3. Other hazards

**Other hazards:** In use, may form flammable / explosive vapour-air mixture.

**PBT:** This product is not identified as a PBT/vPvB substance.

## Section 3: Composition/information on ingredients

### 3.2. Mixtures

#### Hazardous ingredients:

LOW BOILING POINT NAPHTHA - UNSPECIFIED - STODDARD SOLVENT

EINECS	CAS	PBT / WEL	CLP Classification	Percent
232-489-3	8052-41-3	-	Asp. Tox. 1: H304; Flam. Liq. 3: H226; Skin Irrit. 2: H315; Aquatic Chronic 2: H411	10-25%

BARIUM SULPHATE

231-784-4	7727-43-7	Substance with a Community workplace exposure limit.	-	3-5%
-----------	-----------	--	---	------

XYLENE

215-535-7	1330-20-7	-	Flam. Liq. 3: H226; Acute Tox. 4: H332; Acute Tox. 4: H312; Skin Irrit. 2: H315	3-5%
-----------	-----------	---	---	------

CARBON BLACK

215-609-9	1333-86-4	Substance with a Community workplace exposure limit.	-	3-5%
-----------	-----------	--	---	------

## Section 4: First aid measures

### 4.1. Description of first aid measures

**Skin contact:** \* Remove all contaminated clothes and footwear immediately unless stuck to skin.  
Wash immediately with plenty of soap and water.

**Eye contact:** \* Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.

**Ingestion:** \* Wash out mouth with water. Get immediate medical attention.

**Inhalation:** \* Move to fresh air in case of accidental inhalation of vapours.

[cont...]

**SAFETY DATA SHEET**  
151 MATT BLACK PAINT - LOW VOC

Page: 3

**4.2. Most important symptoms and effects, both acute and delayed**

**Skin contact:** There may be mild irritation at the site of contact.

**Eye contact:** There may be irritation and redness.

**Ingestion:** There may be irritation of the throat.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

**4.3. Indication of any immediate medical attention and special treatment needed**

**Immediate / special treatment:** \* Not applicable.

**Section 5: Fire-fighting measures**

**5.1. Extinguishing media**

**Extinguishing media:** Alcohol resistant foam. Water spray. Carbon dioxide. Dry chemical powder.

**5.2. Special hazards arising from the substance or mixture**

**Exposure hazards:** Flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture.

**5.3. Advice for fire-fighters**

**Advice for fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

**Section 6: Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

**Personal precautions:** Refer to section 8 of SDS for personal protection details. Eliminate all sources of ignition.

**6.2. Environmental precautions**

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.

**6.3. Methods and material for containment and cleaning up**

**Clean-up procedures:** Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

**6.4. Reference to other sections**

**Reference to other sections:** Refer to section 8 of SDS.

**Section 7: Handling and storage**

**7.1. Precautions for safe handling**

**Handling requirements:** Do not eat, drink or smoke when using this product. Ensure there is sufficient ventilation of the area.

**7.2. Conditions for safe storage, including any incompatibilities**

**Storage conditions:** Store in a cool, well ventilated area. Keep container tightly closed. Keep away from sources of ignition. KEEP OUT OF THE REACH OF CHILDREN.

[cont...]

**SAFETY DATA SHEET**  
151 MATT BLACK PAINT - LOW VOC

Page: 4

**Suitable packaging:** \* Must only be kept in original packaging.

**7.3. Specific end use(s)**

**Specific end use(s):** No data available.

**Section 8: Exposure controls/personal protection**

**8.1. Control parameters**

**Hazardous ingredients:**

**BARIUM SULPHATE**

**Workplace exposure limits:**

**Respirable dust**

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	-	-	4mg/m3	-

**XYLENE**

UK	220 mg/m3	441 mg/m3	-	-
----	-----------	-----------	---	---

**CARBON BLACK**

UK	3.5mg/m3	7mg/m3	-	-
----	----------	--------	---	---

**DNEL/PNEC Values**

**DNEL / PNEC** No data available.

**8.2. Exposure controls**

**Engineering measures:** Ensure there is sufficient ventilation of the area.

**Respiratory protection:** No special requirements under normal conditions of use. In case of insufficient ventilation, wear an approved respirator gas/vapour filter Type A, organic vapours (EN141).

**Hand protection:** Protective gloves.

**Eye protection:** Safety glasses.

**Skin protection:** No special requirements under normal conditions of use.

**Section 9: Physical and chemical properties**

**9.1. Information on basic physical and chemical properties**

**State:** Liquid

**Colour:** \* Black

**Odour:** Characteristic odour

**Solubility in water:** Insoluble

**Viscosity:** Viscous

**Kinematic viscosity:** 6.60cm<sup>2</sup>/s

**Flash point°C:** 25

**Relative density:** 1.35

**VOC g/l:** 293

[cont...]

**SAFETY DATA SHEET**  
151 MATT BLACK PAINT - LOW VOC

Page: 5

**9.2. Other information**

**Other information:** \* EU Limit value for this product (Cat A/e): 400g/L

**Section 10: Stability and reactivity**

**10.1. Reactivity**

**Reactivity:** Stable under recommended transport or storage conditions.

**10.2. Chemical stability**

**Chemical stability:** Stable under normal conditions. Stable at room temperature.

**10.3. Possibility of hazardous reactions**

**Hazardous reactions:** Hazardous reactions will not occur under normal transport or storage conditions.  
Decomposition may occur on exposure to conditions or materials listed below.

**10.4. Conditions to avoid**

**Conditions to avoid:** Heat. Hot surfaces. Sources of ignition. Flames.

**10.5. Incompatible materials**

**Materials to avoid:** Strong oxidising agents. Strong acids.

**10.6. Hazardous decomposition products**

**Haz. decomp. products:** In combustion emits toxic fumes.

**Section 11: Toxicological information**

**11.1. Information on toxicological effects**

**Hazardous ingredients:**

**BARIUM SULPHATE**

ORAL	RAT (Male)	LD50	>5000	mg/kg
------	------------	------	-------	-------

**XYLENE**

ORL	MUS	LD50	2119	mg/kg
ORL	RAT	LD50	4300	mg/kg
SCU	RAT	LD50	1700	mg/kg

**CARBON BLACK**

DERMAL	RAT	LD50	>8	g/kg
--------	-----	------	----	------

**Relevant hazards for substance:**

Hazard	Route	Basis
--------	-------	-------

[cont...]

**SAFETY DATA SHEET**  
151 MATT BLACK PAINT - LOW VOC

Page: 6

Skin corrosion/irritation	DRM	Hazardous: calculated
Aspiration hazard	-	Hazardous: calculated

**Symptoms / routes of exposure**

**Skin contact:** There may be mild irritation at the site of contact.

**Eye contact:** There may be irritation and redness.

**Ingestion:** There may be irritation of the throat.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

**Section 12: Ecological information**

**12.1. Toxicity**

**Hazardous ingredients:**

**BARIUM SULPHATE**

Daphnia magna	48H EC50	14500	µg/l
ZEBRAFISH (Brachydanio rerio)	96H LC50	>152	mg/l

**XYLENE**

Daphnia magna	IC50	2.2	mg/l
RAINBOW TROUT (Oncorhynchus mykiss)	96H LC50 (Read across)	2.6	mg/l

**CARBON BLACK**

ZEBRAFISH (Danio rerio)	96H LC0	>1000	mg/l
-------------------------	---------	-------	------

**12.2. Persistence and degradability**

**Persistence and degradability:** \* Not readily biodegradable.

**12.3. Bioaccumulative potential**

**Bioaccumulative potential:** \* No data available.

**12.4. Mobility in soil**

**Mobility:** \* Readily absorbed into soil.

**12.5. Results of PBT and vPvB assessment**

**PBT identification:** This product is not identified as a PBT/vPvB substance.

**12.6. Other adverse effects**

**Other adverse effects:** \* Harmful to aquatic organisms.

**Section 13: Disposal considerations**

[cont...]

**SAFETY DATA SHEET**  
151 MATT BLACK PAINT - LOW VOC

Page: 7

**13.1. Waste treatment methods**

**Disposal operations:** Disposal should be in accordance with Local Authority Regulations.

**Disposal of packaging:** Disposal should be in accordance with Local Authority Regulations.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

**Section 14: Transport information**

**14.1. UN number**

**UN number:** \* UN1263

**14.2. UN proper shipping name**

**Shipping name:** PAINT  
(LOW BOILING POINT NAPHTHA - UNSPECIFIED - STODDARD SOLVENT)

**14.3. Transport hazard class(es)**

**Transport class:** 3

**14.4. Packing group**

**Packing group:** III

**14.5. Environmental hazards**

**Environmentally hazardous:** Yes

**Marine pollutant:** No

**14.6. Special precautions for user**

**Special precautions:** No special precautions.

**Tunnel code:** D/E

**Transport category:** 3

**Section 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**Specific regulations:** A REACH registration number is not applicable as this product is a mixture.

**15.2. Chemical Safety Assessment**

**Section 16: Other information**

**Other information**

**Other information:** This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

\* indicates text in the SDS which has changed since the last revision.

**Phrases used in s.2 and s.3:** H226: Flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

H312: Harmful in contact with skin.

[cont...]

## SAFETY DATA SHEET

151 MATT BLACK PAINT - LOW VOC

Page: 8

H315: Causes skin irritation.

H332: Harmful if inhaled.

H411: Toxic to aquatic life with long lasting effects.

H412: Harmful to aquatic life with long lasting effects.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.