

ELBOW GREASE WASHING UP LIQUID

Page: 1

Compilation date: 30/01/2019

Revision date: 30/07/2019

Revision No: 2

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: ELBOW GREASE WASHING UP LIQUID

Product code: EG9, EG10, EG11

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name:	151 Products Ltd
	The Old School House
	39 Bengal Street
	Manchester
	M4 6AF
	United Kingdom
Tel:	+44 (0)161 839 5949
Fax:	+44 (0)161 839 5493
Email:	fereshteh@151.co.uk

1.4. Emergency telephone number

Emergency tel: +44 (0)161 839 5949

(office hours only)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Eye Irrit. 2: H319

Most important adverse effects: Causes serious eye irritation.

2.2. Label elements

Label elements:

Hazard statements: H319: Causes serious eye irritation.

Hazard pictograms: GHS07: Exclamation mark



Signal words: Warning

Precautionary statements: P102: Keep out of reach of children.

P264: Wash hands thoroughly after handling.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove

ELBOW GREASE WASHING UP LIQUID

contact lenses, if present and easy to do. Continue rinsing. P337+P313: If eye irritation persists: Get medical advice/attention. P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting P101: If medical advice is needed, have product container or label at hand. P501: Dispose of contents and container to hazardous or special waste collection point, in accordance with local regulation.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

BENZENESULFONIC ACID, 4-C10-13-SEC-ALKYL DERIVS. - REACH registered number(s): 01-2119490234-40-XXXX

EINECS	CAS	PBT / WEL	CLP Classification	Percent
287-494-3	85536-14-7	-	Aquatic Chronic 3: H412; Skin Corr. 1C: H314; Eye Dam. 1: H318; Acute Tox. 4: H302	1-10%
ALCOHOLS, C	12-14, ETHOXYLA	TED, SULPHATES, SODIUM SALTS		
500-234-8	68891-38-3	-	Skin Irrit. 2: H315; Eye Dam. 1: H318; Aquatic Chronic 3: H412	1-10%
SODIUM HYDI	ROXIDE			·
215-185-5	1310-73-2	-	Skin Corr. 1A: H314	1-10%
COCAMIDE DE	EA			
271-657-0	68603-42-9	_	Skin Irrit. 2: H315; Eye Irrit. 2: H319	1-10%

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin.

Drench the affected skin with running water for 10 minutes or longer if substance is still

on skin. Transfer to hospital if there are burns or symptoms of poisoning.

Eye contact: Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.

Ingestion: Wash out mouth with water. Do not induce vomiting. Give 1 cup of water to drink every 10 minutes. If unconscious, check for breathing and apply artificial respiration if necessary. If unconscious and breathing is OK, place in the recovery position. Transfer to hospital as soon as possible.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. If unconscious and breathing is OK, place in the recovery position. If conscious, ensure

Page: 2

ELBOW GREASE WASHING UP LIQUID

Page: 3

the casualty sits or lies down. If breathing becomes bubbly, have the casualty sit and provide oxygen if available. Transfer to hospital as soon as possible.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: Blistering may occur. Progressive ulceration will occur if treatment is not immediate.

Eye contact: Corneal burns may occur. May cause permanent damage.

- **Ingestion:** Corrosive burns may appear around the lips. Blood may be vomited. There may be bleeding from the mouth or nose.
- **Inhalation:** There may be shortness of breath with a burning sensation in the throat. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray

to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Corrosive. In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Notify the police and fire brigade immediately. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Clean-up should be dealt with only by qualified personnel familiar with the specific substance. Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

ELBOW GREASE WASHING UP LIQUID

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Do not handle in a confined space. Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

SODIUM HYDROXIDE

Workplace exposure limits:

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	-	2 mg/m3	-	-

Respirable dust

DNEL/PNEC Values

Hazardous ingredients:

BENZENESULFONIC ACID, 4-C10-13-SEC-ALKYL DERIVS.

Туре	Exposure	Value	Population	Effect
DNEL	Inhalation	12mg/m ³	Workers	Systemic
DNEL	Inhalation	12mg/m³	Workers	Local
DNEL	Dermal	170mg/kg/day	Workers	Systemic
DNEL	Inhalation	3mg/m³	General Population	Systemic
DNEL	Inhalation	3mg/m³	General Population	Local
DNEL	Dermal	85mg/kg/day	General Population	Systemic
DNEL	Oral	0.85mg/kg/day	General Population	Systemic
PNEC	Fresh water	0.287mg/L	-	-
PNEC	Fresh water sediments	0.287mg/kg	-	-
PNEC	Marine water	0.029mg/L	-	-
PNEC	Marine sediments	0.287mg/kg	-	-

ELBOW GREASE WASHING UP LIQUID

Page: 5

PNEC	STP	3.43mg/L	-	-
PNEC	Soil	35mg/kg	-	-

ALCOHOLS, C12-14, ETHOXYLATED, SULPHATES, SODIUM SALTS

Туре	Exposure	Value	Population	Effect
PNEC	Fresh water	0.24mg/l	-	-
PNEC	Marine water	0.024mg/l	-	-
PNEC	Fresh water sediments	0.917mg/kg	-	-
PNEC	Soil	7.5mg/kg	-	-
DNEL	Inhalation (repeated dose)	175mg/m3	Workers	Systemic
DNEL	Dermal (repeated dose)	2750mg/kg	Workers	Systemic
DNEL	Inhalation (repeated dose)	52mg/m3	General Population	Systemic
DNEL	Dermal (repeated dose)	1650mg/kg	General Population	Systemic
DNEL	Oral (repeated dose)	15mg/kg	General Population	Systemic

SODIUM HYDROXIDE

Туре	Exposure	Value	Population	Effect
DNEL	Inhalation (Long term exposure)	1mg/m3	Workers	Local
DNEL	Inhalation (Long term exposure)	1mg/m3	General Population	Local

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Impermeable gloves.

Eye protection: Tightly fitting safety goggles. Ensure eye bath is to hand.

Skin protection: Impermeable protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

ELBOW GREASE WASHING UP LIQUID

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

BENZENESULFONIC ACID, 4-C10-13-SEC-ALKYL DERIVS.

DERMAL	RAT	LD50 (Read Across)	>2000	mg/kg	
ORAL	RAT	LD50	1470	mg/kg	

ALCOHOLS, C12-14, ETHOXYLATED, SULPHATES, SODIUM SALTS

ORAL RAT LD50 4100 mg/kg	
--------------------------	--

SODIUM HYDROXIDE

IPR	MUS	LD50	40	mg/kg
ORL	RBT	LDLO	500	mg/kg

COCAMIDE DEA

ORAL RAT LD50	>3000 mg/kg	
---------------	-------------	--

Relevant hazards for product:

Hazard	Route	Basis
Serious eye damage/irritation	OPT	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: Blistering may occur. Progressive ulceration will occur if treatment is not immediate.

Eye contact: Corneal burns may occur. May cause permanent damage.

- **Ingestion:** Corrosive burns may appear around the lips. Blood may be vomited. There may be bleeding from the mouth or nose.
- **Inhalation:** There may be shortness of breath with a burning sensation in the throat. Exposure may cause coughing or wheezing.
- **Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

ELBOW GREASE WASHING UP LIQUID

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

BENZENESULFONIC ACID, 4-C10-13-SEC-ALKYL DERIVS.

BLUEGILL (Lepomis macrochirus)	96H LC50	1.67	mg/l
Daphnia magna	48H EC50	2.9	mg/l
GREEN ALGA (Selenastrum capricornutum)	96H ErC50	29	mg/l

ALCOHOLS, C12-14, ETHOXYLATED, SULPHATES, SODIUM SALTS

ALGAE (Desmodesmus subspicatus)	72H ErC50	27	mg/l
Pseudomonas putida	16H EC50	>10	g/l
WATER FLEA (Daphnia magna)	48H EC50	7.2	mg/l
ZEBRAFISH (Brachydanio rerio)	96H LC50	7.1	mg/l

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

Section 14: Transport information

Transport class: This product does not require a classification for transport.

Section 15: Regulatory information

ELBOW GREASE WASHING UP LIQUID

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

Section 16: Other information

Other information	
Other information:	according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation
	(EU) 2015/830
	* indicates text in the SDS which has changed since the last revision.
Phrases used in s.2 and s.3:	H302: Harmful if swallowed.
	H314: Causes severe skin burns and eye damage.
	H315: Causes skin irritation.
	H318: Causes serious eye damage.
	H319: Causes serious eye irritation.
	H412: Harmful to aquatic life with long lasting effects.
Legal disclaimer:	The above information is believed to be correct but does not purport to be all inclusive
	and shall be used only as a guide. This company shall not be held liable for any
	damage resulting from handling or from contact with the above product.