



# SAFETY DATA SHEET

151 MULTIPURPOSE SPRAY PAINT - GREEN

Page: 1  
Compilation date: 31/10/2017  
Revision No: 1

## Section 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

**Product name:** 151 MULTIPURPOSE SPRAY PAINT - GREEN  
**Product code:** TAR042

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Use of substance / mixture:** SU 21 - Consumer Uses. PC9a: Coatings and paints, thinners, paint removers.

### 1.3. Details of the supplier of the safety data sheet

**Company name:** 151 Products Limited  
The Old School House  
39 Bengal Street  
Manchester  
M4 6AF  
UK  
**Tel:** 0161 839 5949  
**Fax:** 0161 839 5493  
**Email:** [fereshteh@151.co.uk](mailto:fereshteh@151.co.uk)

### 1.4. Emergency telephone number

## Section 2: Hazards identification

### 2.1. Classification of the substance or mixture

**Classification under CLP:** Eye Irrit. 2: H319; Flam. Aerosol 1: H222; STOT SE 3: H336; -: H229

**Most important adverse effects:** Extremely flammable aerosol. Pressurised container: May burst if heated. Causes serious eye irritation. May cause drowsiness or dizziness.

### 2.2. Label elements

#### Label elements:

**Hazard statements:** H222: Extremely flammable aerosol.  
H229: Pressurised container: May burst if heated  
H319: Causes serious eye irritation.  
H336: May cause drowsiness or dizziness.

**Hazard pictograms:** GHS02: Flame  
GHS07: Exclamation mark



**Signal words:** Danger

# SAFETY DATA SHEET

151 MULTIPURPOSE SPRAY PAINT - GREEN

Page: 2

**Precautionary statements:** P102: Keep out of reach of children.  
P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211: Do not spray on an open flame or other ignition source.  
P251: Do not pierce or burn, even after use.  
P261: Avoid breathing mist and spray.  
P264: Wash hands thoroughly after handling.  
P271: Use only outdoors or in a well-ventilated area.  
P304+340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P410+412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C.  
P501: Dispose of contents/container to Local authority regulations.

## 2.3. Other hazards

**PBT:** This product is not identified as a PBT/vPvB substance.

## Section 3: Composition/information on ingredients

### 3.2. Mixtures

#### Hazardous ingredients:

##### DIMETHYL ETHER

EINECS	CAS	PBT / WEL	CLP Classification	Percent
204-065-8	115-10-6	Substance with a Community workplace exposure limit.	Flam. Gas 1: H220; Press. Gas: H280	25-50%

##### N-BUTYL ACETATE

204-658-1	123-86-4	-	Flam. Liq. 3: H226; STOT SE 3: H336; -: EUH066	10-25%
-----------	----------	---	--	--------

##### ACETONE

200-662-2	67-64-1	-	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; -: EUH066	5-10%
-----------	---------	---	--	-------

##### 2-BUTOXYETHANOL

203-905-0	111-76-2	-	Acute Tox. 4: H332; Acute Tox. 4: H312; Acute Tox. 4: H302; Eye Irrit. 2: H319; Skin Irrit. 2: H315	3-5%
-----------	----------	---	---	------

##### ETHYL ACETATE

205-500-4	141-78-6	-	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; -: EUH066	1-3%
-----------	----------	---	--	------

## Section 4: First aid measures

[cont...]

# SAFETY DATA SHEET

151 MULTIPURPOSE SPRAY PAINT - GREEN

Page: 3

## 4.1. Description of first aid measures

**Skin contact:** Wash immediately with plenty of soap and water.

**Eye contact:** Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.

**Ingestion:** Wash out mouth with water. Consult a doctor.

**Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so.

## 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat.

**Inhalation:** Exposure may cause coughing or wheezing. There may be irritation of the nose and upper respiratory tract.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

## 4.3. Indication of any immediate medical attention and special treatment needed

## Section 5: Fire-fighting measures

### 5.1. Extinguishing media

**Extinguishing media:** Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

### 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** In combustion emits toxic fumes. Vapour may travel considerable distance to source of ignition and flash back. Pressurized container may explode in the heat of a fire.

### 5.3. Advice for fire-fighters

**Advice for fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

## Section 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions:** Refer to section 8 of SDS for personal protection details. Turn leaking containers leak-side up to prevent the escape of liquid.

### 6.2. Environmental precautions

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.

### 6.3. Methods and material for containment and cleaning up

**Clean-up procedures:** Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

[cont...]

# SAFETY DATA SHEET

151 MULTIPURPOSE SPRAY PAINT - GREEN

Page: 4

## 6.4. Reference to other sections

**Reference to other sections:** Refer to section 8 of SDS.

## Section 7: Handling and storage

### 7.1. Precautions for safe handling

**Handling requirements:** Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.  
Do not handle in a confined space.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage conditions:** Store in a cool, well ventilated area. KEEP OUT OF THE REACH OF CHILDREN.  
**Suitable packaging:** Must only be kept in original packaging.

### 7.3. Specific end use(s)

**Specific end use(s):** No data available.

## Section 8: Exposure controls/personal protection

### 8.1. Control parameters

**Hazardous ingredients:**

**DIMETHYL ETHER**

**Workplace exposure limits:**

**Respirable dust**

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	766 mg/m <sup>3</sup>	958 mg/m <sup>3</sup>	-	-

**N-BUTYL ACETATE**

UK	724 mg/m <sup>3</sup>	966 mg/m <sup>3</sup>	-	-
----	-----------------------	-----------------------	---	---

**ACETONE**

UK	1210 mg/m <sup>3</sup>	3620 mg/m <sup>3</sup>	-	-
----	------------------------	------------------------	---	---

**2-BUTOXYETHANOL**

UK	25 ppm	50 ppm	-	-
----	--------	--------	---	---

**ETHYL ACETATE**

UK	200 ppm	400 ppm	-	-
----	---------	---------	---	---

### DNEL/PNEC Values

**DNEL / PNEC** No data available.

### 8.2. Exposure controls

**Engineering measures:** Ensure there is sufficient ventilation of the area.

**Respiratory protection:** In case of insufficient ventilation, wear an approved respirator gas/vapour filter Type A, organic vapours (EN141).

**Hand protection:** Protective gloves.

[cont...]

# SAFETY DATA SHEET

151 MULTIPURPOSE SPRAY PAINT - GREEN

Page: 5

**Eye protection:** Safety glasses.

**Skin protection:** No special requirements under normal conditions of use.

## Section 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

**State:** Aerosol

**Colour:** Green

**Odour:** Solvent.

**Solubility in water:** Insoluble

### 9.2. Other information

**Other information:** No data available.

## Section 10: Stability and reactivity

### 10.1. Reactivity

**Reactivity:** Stable under recommended transport or storage conditions.

### 10.2. Chemical stability

**Chemical stability:** Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

**Hazardous reactions:** Hazardous reactions will not occur under normal transport or storage conditions.  
Decomposition may occur on exposure to conditions or materials listed below.

### 10.4. Conditions to avoid

**Conditions to avoid:** Heat. Sources of ignition. Flames.

### 10.5. Incompatible materials

**Materials to avoid:** Strong oxidising agents. Strong acids.

### 10.6. Hazardous decomposition products

**Haz. decomp. products:** In combustion emits toxic fumes.

## Section 11: Toxicological information

### 11.1. Information on toxicological effects

**Hazardous ingredients:**

**N-BUTYL ACETATE**

ORL	MUS	LD50	6	gm/kg
ORL	RAT	LD50	10768	mg/kg

[cont...]

# SAFETY DATA SHEET

151 MULTIPURPOSE SPRAY PAINT - GREEN

Page: 6

## ACETONE

IVN	RAT	LD50	5500	mg/kg
ORL	MUS	LD50	3000	mg/kg
ORL	RAT	LD50	5800	mg/kg

## 2-BUTOXYETHANOL

IVN	RAT	LD50	307	mg/kg
ORL	MUS	LD50	1230	mg/kg
ORL	RAT	LD50	470	mg/kg

## ETHYL ACETATE

ORL	MUS	LD50	4100	mg/kg
ORL	RAT	LD50	5620	mg/kg
SCU	RAT	LDLO	5	gm/kg

### Relevant hazards for product:

Hazard	Route	Basis
Serious eye damage/irritation	OPT	Hazardous: calculated
STOT-single exposure	-	Hazardous: calculated

### Symptoms / routes of exposure

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat.

**Inhalation:** Exposure may cause coughing or wheezing. There may be irritation of the nose and upper respiratory tract.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

## Section 12: Ecological information

### 12.1. Toxicity

#### Hazardous ingredients:

#### ACETONE

BLUEGILL ( <i>Lepomis macrochirus</i> )	LC50	8300	mg/l
---	------	------	------

### 12.2. Persistence and degradability

**Persistence and degradability:** Partially biodegradable

### 12.3. Bioaccumulative potential

**Bioaccumulative potential:** No data available.

[cont...]

# SAFETY DATA SHEET

151 MULTIPURPOSE SPRAY PAINT - GREEN

Page: 7

## 12.4. Mobility in soil

**Mobility:** Insoluble in water.

## 12.5. Results of PBT and vPvB assessment

**PBT identification:** This product is not identified as a PBT/vPvB substance.

## 12.6. Other adverse effects

**Other adverse effects:** Negligible ecotoxicity.

## Section 13: Disposal considerations

### 13.1. Waste treatment methods

**Disposal operations:** Disposal should be in accordance with Local Authority Regulations. Do not pierce containers prior to disposal.

**Disposal of packaging:** Disposal should be in accordance with Local Authority Regulations.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

## Section 14: Transport information

### 14.1. UN number

**UN number:** UN1950

### 14.2. UN proper shipping name

**Shipping name:** AEROSOLS

### 14.3. Transport hazard class(es)

**Transport class:** 2

### 14.4. Packing group

### 14.5. Environmental hazards

**Environmentally hazardous:** No

**Marine pollutant:** No

### 14.6. Special precautions for user

**Special precautions:** No special precautions.

**Tunnel code:** D

**Transport category:** 2

## Section 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**Specific regulations:** Not applicable.

### 15.2. Chemical Safety Assessment

[cont...]

# SAFETY DATA SHEET

151 MULTIPURPOSE SPRAY PAINT - GREEN

Page: 8

## Section 16: Other information

### Other information

**Other information:** This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.

\* indicates text in the SDS which has changed since the last revision.

**Phrases used in s.2 and s.3:** EUH066: Repeated exposure may cause skin dryness or cracking.

H220: Extremely flammable gas.

H222: Extremely flammable aerosol.

H225: Highly flammable liquid and vapour.

H226: Flammable liquid and vapour.

H229: Pressurised container: May burst if heated

H302: Harmful if swallowed.

H312: Harmful in contact with skin.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H336: May cause drowsiness or dizziness.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.